

The Light Source

Mega-Coupler



Pictured above -

The standard Black Mega-Coupler # MLB. Has a 1/2" x 1 1/4" Hex Head Bolt with the Light Source Wing Nut.

Our Mega-Coupler has solid nut tabs that won't break off. Mega-Coupler uses standard half inch by 1-1/4 inch long hex head grade 8 bolts to secure your load. Bolt head locks into hex milled pocket so that you can tighten the nyloc nut while the damp is installed. Has industry compatible 14 mm thick base. The Mega-Coupler fastens from (1-1/4" Pipe) 1.66" OD to 2" OD truss tube.

Mega-Coupler Options -

- 1/2" x 1 1/4" Hex Head Bolt with Nylock Nut (Standard Mega-Coupler pictured above)
- 1/2" countersunk (CS) flat head bolt (see Mega-Coupler with Flat Head Bolt.)
- 3/8" countersunk (CS) flat head bolt (see Mega-Coupler with Flat Head Bolt)
- 3/8" x 1" Hex Head Bolt (3/8)
- 1/2" x 1 1/4" stainless steel (SS) bolt
- 1/2" x 1 1/4" steel wingnut (SW)



Minimum Size	1.25" pipe, 1.66" OD pipe
Maximum Size	1.5" pipe, 1.90" OD pipe, 2" OD truss tube
Safe Vertical Working Load	1,100 lb 500kg
Hardware	Standard hardware - 1/2-13 x 1 1/4" Hex Head grade 8 zinc plated steel bolt with nylock nut 1" Belleville Washer
Weight	1.2 Pounds
Case Quantities	24

