

The Light Source

Quad Coupler 1.5



The Quad Coupler 1.5 will clamp from 1.25" OD to 1.5" OD tubing as well as 1" pipe (1.315" OD.) The Quad Coupler 1.5 is 1.25" thick. The notch on the outside of clamp is 1.26" across the flats and will fit over 1-1/4" square tube, while locking the clamp parallel with the 1-1/4" square tubing. Use the flat face to bolt to a fixture, or to allow the Quad Coupler 1.5 to rotate when fastened to square tubing. The distance from the bottom of the clamped pipe or tube, to the flat or notched connecting surface, is .84" Complete with 3/8" x 1.25" socket head cap screw with nylon insert lock nut and Belleville spring washer.

Minimum Size	1.25" OD tube, 1" pipe, 1.315" OD pipe
Maximum Size	1.5" OD tube
Safe Vertical Working Load	770 Pounds
Hardware	3/8"-16tpi x 1.25" Socket Head Cap Screw. 3/8" nylon insert lock nut. Belleville Washer.
Diminsions	1.25" Thick
Weight	.5 lb.
Case Quantities	12 or 24
Order Codes	QCI.5M Quad Coupler 1.5, Aluminum Finish QCI.5B Quad Coupler 1.5, Black Anodized