

# The Light Source

## Coupler with Eye Nut



The Mega-Coupler with Eye Nut has a Forged Steel Eye Nut for making rigging connections from a pipe or truss. The Forged Eye Nut is secured to the Mega-Coupler with a 1/2" flathead socket screw with permanent loctite. The Eye Nut rigging connection is 2-3/4" below the pipe and is able to swivel for proper orientation before loading. The Mega-Coupler will fasten from 1-1/4" pipe (1.660" OD) to 2.050" OD truss tube. The Mega-Coupler has our wide wing nut for fastening the clamp to the pipe or tube. Safe Vertical Working Load 1100 Pounds, (500 KG).

<b>Minimum Size</b>	1.25" pipe, 1.66" OD pipe
<b>Maximum Size</b>	1.5" pipe, 1.90" OD pipe, 2" OD truss tube
<b>Working Load Limit</b>	1100 Pounds
<b>Hardware</b>	Forged steel eye nut. 1/2" flathead socket screw with permanent loctite.
<b>Dimensions</b>	2.5" Tall 2" Wide .4" Thick I.D. of 1.2" Wide I.D. of 1.5" Tall The I.D. is pear shaped
<b>Weight</b>	1.3 Pounds
<b>Case Quantities</b>	24
<b>Order Codes</b>	<b>MLMSE</b> Mega-Coupler with Eye Nut, Silver <b>MLBSE</b> Mega-Coupler with Eye Nut, Black Anodized <b>MLMSE-SW</b> Mega-Coupler with Eye Nut, Steel Wing Nut, Silver <b>MLBSE-SW</b> Mega-Coupler with Eye Nut, Steel Wing Nut, Black Anodized <b>MLWSE</b> Mega-Coupler with Eye Nut, White Powder Coat