# The Light Source
# 8" Mega-Beam Clamp - 2 Ton



The Mega-Beam Clamp is a low profile, sliding jaw design that allows the load to be secured as closely as possible to the I-beam. The 8" model is load rated for 2 tons.

Two aircraft aluminum jaws are adjusted on the 3/4"-6 TPI Acme threaded shaft. The spring loaded handle locks after adjustment. The center hole is 1 1/2".

The Mega-Beam Clamp fastens from 2" to 8" wide on I-beam flanges up to 1" thick. For I-beam flanges up to 2" thick, Mega-Beam Clamps are available with 2" jaws. The 2" jaws may also be purchased separately.

The aluminum construction is half the weight of steel units and has a wider gripping range.

The Mega-Beam Clamp can be used for both permanent and temporary installations.

The 8" Mega-Beam Clamp is available with 2 attached Mega-Couplers. The design load limits of the Mega-Couplers de-rate the load limit to 1 ton. Also, the load must be evenly distributed.

| | |
|---|---|
| **Working Load Limit** | 4,000 lbs. / 1818 kg |
| **Dimensions** | 14" L x 7.5" T x 2.75" W; Center Hole - 1 1/2" |
| **Weight** | 10.25 Pounds |
| **Case Quantities** | Each |

**Order Codes**

**MBC1T-8B-MLM** 8" Mega-Beam Clamp with 2 Mega-Couplers, Black
**MBC1T-8M-MLM** 8" Mega-Beam Clamp with 2 Mega-Couplers, Silver
**MBC2T-8B** 8" Mega-Beam Clamp, Black
**MBC2T-8B-2** 8" Mega-Beam Clamp with 2" Jaws, Black
**MBC2T-8M** 8" Mega-Beam Clamp, Silver
**MBC2T-8M-2** 8" Mega-Beam Clamp with 2" Jaws, Silver

The Light Source, Inc. 3935 Westinghouse Blvd. Charlotte, NC 28273 Phone: 704-504-8399 Fax: 704-588-4637
www.thelightsource.com