The Light Source
Mega-Truss Pick for Threaded Rod Installations



12" Threaded Rod Truss Pick pictured above -

Two 1" x 2" x 15" 6061T-6 aluminum bars CNC machined with pockets to support one piece of 12" truss. The Mega-Truss Pick will suspend up to one ton of truss load when the Mega-Truss Pick is suspended by two customer supplied 1/2" threaded rods, or two 1/2" forged steel shoulder eyebolts fastened through the outside support holes. All of the holes are through holes without threading. Secure the threaded rod with a nut and washers above and use a nyloc nuts with a USS washer below the truss pick.

Rigging from only the center hole de-rates the Threaded Rod Truss Pick to 250 pounds capacity.

Priced per pair.

Available in 12", 16", 18", 20.5" sizes.
11.4375" for Global Truss.

The WLL applies to all sizes.

Working Load Limit	2000 lbs with two outside 1/2" threaded rods
Dimensions	1" x 2" x 21" (18 inch)1" x 2" x 15" (12 inch)
Weight	12" - 5 lbs. 18" - 7 lbs.
Case Quantities	each pair

Order Codes

MTPTR11.4375 Mega-Truss Pick 11.4375 inch for Threaded Rod Installations, Silver
MTPTR11.4375B Mega-Truss Pick 11.4375 for Threaded Rod Installations, Black Anodized
MTPTR12B Mega-Truss Pick 12 inch for Threaded Rod Installations, Black Anodized
MTPTR12M Mega-Truss Pick 12 inch for Threaded Rod Installations, Silver
MTPTR12W Mega-Truss Pick 12 inch for Threaded Rod Installations, White Powder Coat
MTPTR16M Mega-Truss Pick 16 inch for Threaded Rod Installations,, Silver
MTPTR18M Mega-Truss Pick 18 inch for Threaded Rod Installations, Silver
MTPTR20.5B Mega-Truss Pick, Install 20.5", Black, Black
MTPTR20.5M Mega-Truss Pick 20.5 inch for Threaded Rod Installations, Silver

The Light Source, Inc. 3935 Westinghouse Blvd. Charlotte, NC 28273 Phone: 704-504-8399 Fax: 704-588-4637
www.thelightsource.com