The Light Source
Uni-Bolt for Strut Channels



The Uni-Bolt fastens fixtures or pipes to strut channel. Insert the Uni-Bolt into the strut channel, rotate 90 degrees and spin the 2" diameter knurled disk to lock into the channel. Also available for 1 5/8" x 13/16" strut channel.

The UB2B works with Uni-Strut product series: P1000, P1100, P2000, P3000, P5000, and P5500

The UB2B2 works with Uni-strut product series: P3300, P4000, and P4100

Minimum Size	1 5/8" x 1 5/8" Strut Channel
Working Load Limit	250 lbs.
Hardware	1/2-13 TPI x 1" Hex Head Cap Screw Grade 5 Zinc Plated.
Weight	0.35 lbs.
Case Quantities	each

Order Codes

UB2B Uni-Bolt for Strut Channels, Black
UB2B-M10 Uni-Bolt for Strut Channels with M10 Threads, Black
UB2B2 Low Profile Uni-Bolt for Strut Channels 1 5/8" x 13/16", Black
UB2W Uni-Bolt for Strut Channels, White Powder Coat
UB2W2 Low Profile Uni-Bolt for Strut Channels 1 5/8" x 13 /16", White Powder Coat

The Light Source, Inc. 3935 Westinghouse Blvd. Charlotte, NC 28273 Phone: 704-504-8399 Fax: 704-588-4637
www.thelightsource.com