

# The Light Source Coupler with Eye Nut



The Mega-Coupler with Eye Nut has a Forged Steel Eye Nut for making rigging connections from a pipe or truss. The Forged Eye Nut is secured to the Mega-Coupler with a 1/2" flathead socket screw with permanent loctite. The Eye Nut rigging connection is 2-3/4" below the pipe and is able to swivel for proper orientation before loading. The Mega-Coupler will fasten from 1-1/4" pipe (1.660" OD) to 2.050" OD truss tube. The Mega-Coupler has our wide wing nut for fastening the clamp to the pipe or tube. Safe Vertical Working Load 1100 Pounds, (500 KG).

**Minimum Size**

1.25" pipe, 1.66" OD pipe

**Maximum Size**

1.5" pipe, 1.90" OD pipe, 2" OD truss tube

**Working Load Limit**

1100 Pounds

**Hardware**

Forged steel eye nut.  
1/2" flathead socket screw with permanent loctite.

**Dimensions**

2.5" Tall 2" Wide 4" Thick I.D. of 1.2" Wide I.D. of 1.5" Tall The I.D. is pear shaped

**Weight**

1.3 Pounds

**Case Quantities**

24

**Order Codes**

**MLMSE** Mega-Coupler with Eye Nut, Silver  
**MLBSE** Mega-Coupler with Eye Nut, Black Anodized  
**MLMSE-SW** Mega-Coupler with Eye Nut, Steel Wing Nut, Silver  
**MLBSE-SW** Mega-Coupler with Eye Nut, Steel Wing Nut, Black Anodized  
**MLWSE** Mega-Coupler with Eye Nut, White Powder Coat