

The Light Source Coupler with Eye Nut



The Mega-Coupler with Eye Nut has a Forged Steel Eye Nut for making rigging connections from a pipe or truss. The Forged Eye Nut is secured to the Mega-Coupler with a 1/2" flathead socket screw with permanent loctite. The Eye Nut rigging connection is 2-3/4" below the pipe and is able to swivel for proper orientation before loading. The Mega-Coupler will fasten from 1-1/4" pipe (1.660" OD) to 2.050" OD truss tube. The Mega-Coupler has our wide wing nut for fastening the clamp to the pipe or tube. Safe Vertical Working Load 1100 Pounds, (500 KG).

Minimum Size	1.25" pipe, 1.66" OD pipe
Maximum Size	1.5" pipe, 1.90" OD pipe, 2" OD truss tube
Working Load Limit	1100 Pounds
Hardware	Forged steel eye nut. 1/2" flathead socket screw with permanent loctite.
Dimensions	2.5" Tall 2" Wide 4" Thick I.D. of 1.2" Wide I.D. of 1.5" Tall The I.D. is pear shaped
Weight	1.3 Pounds
Case Quantities	24

Order Codes	MLMSE Mega-Coupler with Eye Nut, Silver
	MLBSE Mega-Coupler with Eye Nut, Black Anodized
	MLBSE-SW Mega-Coupler with Eye Nut, Steel Wing Nut, Black Anodized
	MLMSE-SW Mega-Coupler with Eye Nut, Steel Wing Nut, Silver
	MLWSE Mega-Coupler with Eye Nut, White Powder Coat