## The Light Source Mega-Swivel Coupler



The Swivel Coupler will fasten from 1-1/4" pipe (1.660" OD) to 2.050" OD truss tube. The Swivel-Coupler has wide wing nuts for fastening the clamp to the pipe or tube.

The Swivel Coupler can be locked into a 90 degree fixed coupler by adding an optional 7/32" x 2" spirol pin.

The Swivel Coupler is available with a Steel Wingnut(SW), and Stainless Steel Hardware (SS) options.

Minimum Size 1.25" pipe, 1.66" OD pipe

Maximum Size 1.5" pipe, 1.90" OD pipe, 2" OD truss tube

Working Load Limit 1,100 Pounds 500kg

Weight 2.2 Pounds

Case Quantities 12

**Order Codes** 

MLSM Mega-Coupler, Swivel, Silver

MLSB Mega-Coupler, Swivel, Black Anodized

MLSM-SW Mega-Coupler, Swivel with Steel Wingnut, Silver

MLSM-SS Mega-Coupler, Swivel with Stainless Steel Hardware, Silver MLSB-SW Mega-Coupler, Swivel with Steel Wingnut, Black Anodized

MLSB-SS Mega-Coupler, Swivel with Stainless Steel Hardware, Black Anodized

MLSW Mega-Coupler, Swivel, White Powder Coat

MLSB-NN Mega-Coupler, Swivel, Nylock Nut, Black Anodized

**MLSB-SS-NN** Mega-Coupler, Swivel with Stainless Steel Hardware and Nylock Nut on the Bolt Assembly, Black

**MLSM-SS-NN** Mega-Coupler, Swivel with Stainless Steel Hardware & Nylock Nut on the Bolt Assembly. Silver

**MLSB-SS-SW** Mega-Coupler, Swivel with Stainless Steel Hardware, and Stainless Steel Wingnut, Black Anodized

**MLSM-SS-SW** Mega-Coupler, Swivel with Stainless Steel Hardware, and Stainless Steel Wingnut, Silver