

The Light Source

Mega-Coupler



The Mega-Coupler has solid wing nut tabs that are stronger than regular steel wing nuts. The grade 8 Hex Head Cap Screw locks securely into the hex milled pocket so that the nylock nut can be tightened while the damp is installed

The Mega-Coupler fastens from (1-1/4" Pipe) 1.66" OD to 2" OD truss tube and has the industry compatible 14 mm thick base.

Although 1/2" is the most frequently used hardware size, the Mega-Coupler also comes in a 3/8" and 1/4" size. Other Mega-Coupler options include stainless steel hardware, steel wing nuts, Metric M-12 and M-10 hardware.

For countersunk Mega-Couplers, see the Flat Head Mega-Coupler section.

For replacement parts, see the Spare Parts section.

Minimum Size	1.25" pipe, 1.66" OD pipe
Maximum Size	1.5" pipe, 1.90" OD pipe, 2" OD truss tube
Working Load Limit	1,100 lb 500kg, for 1/2" and 3/8" hardware 450 lb for 1/4" hardware
Hardware	Standard hardware - 1/2-13 x 1 1/4" Hex Head grade 8 zinc plated steel bolt with nylock nut 1" Belleville Washer
Weight	1.14 lbs. (MLB-NN – 1.11 lbs.) (MLB3/8 – 1.07 lbs.)
Case Quantities	24